




# THE JACK - ACDC Tribute

## Technical Rider



SB Stage Box    
 A.C. Alternating Current    
 Monitor    
 SideFill

THE JACK	CHANNEL LIST		
N°	Instrument	Micro	Channel Name
1	Kick In	Beta 91	K in
2	Kick Out	Beta 52	K out
3	Snare Top	SM 57	S top
4	Snare Bottom	SM 57	S bot
5	Tom 1	BeyerDynamic TG D58 / Sennheiser E604	T 1
6	Tom 2	BeyerDynamic TG D58 / Sennheiser E604	T 2
7	Floor Tom	BeyerDynamic TG D58 / Sennheiser E604	T 3
8	Charleston	AudioTechnica ATM450	Hh

THE JACK		CHANNEL LIST	
N°	Instrument	Micro	Channel Name
9	OverHead L	AKG 414	Oh L
10	OverHead R	AKG 414	Oh R
12	Bass	DI	B
13	El. Guitar	DI	Gtr L
21	Vox 1	Beta 58 (QLXD Wireless)	V 1
22	Vox 2	Beta 58	V 2
23	Vox 3	Beta 58	V 3
24	Spare Vox 1	Beta 58	Sp 1
25	Spare Vox 2	Beta 58	Sp 2

THE JACK		SEND LIST	
Aux / Matrix	Monitor	Type	
M 1	SideFill L	Top + Sub	
M 2	SideFill R	Top + Sub	
A 1	Bass	Stage Monitor	
A 2	Guitar/Vox	Stage Monitor	
A 3	Saxo/Vox 3	Stage Monitor	
A 4	Keys2/Vox 2	Stage Monitor	
A 5	Drum	Stage Monitor	

## PA System

The sound system that we need is a system composed of Top and Sub able to cover the entire range of frequencies, perfectly aligned, which generates a pressure of 110/115 dB in the FOH Control and in the surrounding area dedicated to the public.

**PA Systems** (in order of preference): Meyer, L-Acoustics, JBL, ElectroVoice, dB Tech.  
Preferred **Communication System**: DANTE used in Redundant Mode.

## FOH Control

The FOH Control must be located in front of the stage at a distance appropriate to the size of the stage structure.

**Main Mixer** (in order of preference): Yamaha CL5, QL5, TF5.  
**Talkback**: Sm58 + Microphone Stand

## STAGE Control (when necessary)

The STAGE Control must be placed on the side of the stage in a position that allows the technician and the musicians to be able to see each other at any time.

**Stage Mixer** (in order of preference): Yamaha QL5, QL3, TF5.  
**Talkback**: Sm58 + Microphone Stand

## Monitor System

The requested Monitor System must be composed of a SideFill formed by Top + Sub with a power of at least 4000 Watts and 5 Stage Monitors of the power of at least 500 watts each.

**SideFill** (in order of preference): Meyer, L-Acoustics, JBL, QSC.  
Preferred **Stage Monitors**: Martin, Meyer, dB Technologies, QSC, RCF.

## Contacts

Task	Name	Phone	email
Management	Ale Ronzani	+39 339 287 15 35	<a href="mailto:parallelstudios.info@gmail.com">parallelstudios.info@gmail.com</a>

